





## **EYEMAX**

SINGLE-USE VIDEO CHOLANGIOPANCREATICOSCOPY









## HIGH-PERFORMANCE PROCESSOR

#### **EFFICIENT IMAGE PROCESSING**

- High-quality video image signal
- Easy to operate user interface
- Image enlargement up to 3x
- Adjustable display of the visualisation

#### **EXCELLENT IMAGE QUALITY**

The EYEMAX cholangioscope enables excellent high resolution image quality for improved visualisation of the bile and pancreatic ducts which can reduce the number of examinations.







8 MICRO-TECH 9

### **HARNESS**

#### FOR MAXIMUM USER COMFORT

- Ergonomic alternative for conventional secure fixing
- Relief during longer examinations as the weight of the cholangio- and duodenoscope do not have to be held in one hand
- One-hand operation of the cholangioscope guaranteed





Secure fixing is achieved by the anchor on the handle of the cholangioscope and attachment to the harness.



The cholangioscope is latched and secured to the harness to enable one-hand operation.



## **COMPATIBLE ACCESSORIES**

# FOR SUCCESSFULL PROCEDURES AND OUTCOMES

- Large working channel with 1.2 mm or 2.0 mm diameter for conclusive samples and easier sampling
- Easy insertion of forceps even with a bent endoscope due to the short, rigid distal end of the forceps
- In addition to the irrigation channels, fluids can also be injected via the working channel

#### **SPECIFICATIONS**

	REF		max. catheter Ø mm Worl		orking channel Ø mm		Working length mm		
	CHOLANGIOSCOPES PERORAL								
	CDS11006	511006		3.9		2.0		2200	
7	CDS22006	3.2			1.2			2200	
PERORAL	Packing unit: 1 piece								
	REF	min. working channel Ø mm	Length mm	Opening width mm	Jaw Ø mm	Spike	Covering	Туре	
4	ACCESSORIES (FORCEPS) PERORAL								
	BF10006	1.1	2900	3.0	1.0	Without	PTFE	Alligator	
	BF16006	1.8	2900	4.5	1.6	Without	PE	Alligator	
	Packing unit: 2 pieces								

	REF I		max. catheter Ø mm Wor		Vorking channel Ø mm		Working length mm		
	CHOLANGIOSCOPES PERCUTANEOUS								
US	CDS11005 3.9		3.9	2.0			650*		
8	CDS22005	3.2			1.2			650*	
Ā	Packing unit: 1 piece								
<b>PERCUTANEOUS</b>	REF	min. working channel Ø mm	Length mm	Opening width mm	Jaw Ø mm	Spike	Covering	Туре	
낊	ACCESSORIES (FORCEPS) PERCUTANEOUS								
ם	BF10001	1.1	1200	3.0	1.0	Without	PTFE	Alligator	
	BF16001	1.8	1200	4.5	1.6	Without	PE	Alligator	
	Packing unit: 2 pieces								

<sup>\*</sup> Please note: The harness is not suitable for 650 mm cholangioscopes.

REF	Sterilization	Frequency of use	
HARNESS			
409501002	EO treated	Single use only	

Packing unit: 1 piece

REF	Interfaces	Dimensions (LxWxH) mm	Power supply	Weight
PROCESSOR				
BS-W-100	DVI-D, Composite	355 x 297 x 107	230V	6 kg
CABLE**				
996-17913-0300	DVI-cable	L 3000		
996-17907-0300	BNC-cable	L 3000		
Packing unit: 1 piece				

 $<sup>\</sup>ensuremath{^{**}}$  Please note: when ordering a processor, please specify both cables.

REF	Country
POWER CORD***	
BS100-TYPE D	Algeria, Angola, Egypt, Iraq, Lebanon, Libya, Morocco, Mozambique, Oman, South Africa, Sudan
BS100-TYPE G	Great Britain, Ireland, Jordan, Kenya, Kuwait, Malta, Qatar, Saudi Arabia, Uganda, United Arab Emirates
BS100-TYPE H	Israel, Palestine
BS100-TYPE J	Switzerland
BS100-TYPE K	Denmark
BS100-TYPE L	Italy, Syria
Packing unit: 1 piece	

<sup>\*\*\*</sup> Please note: Choose the correct power cord for your country when ordering. For other countries the type E power cord is already included.

10 MICRO-TECH 11

